

UNI-TAP

AVAILABLE MATERIALS

- High strength nylon

FEATURES/ADVANTAGES


- Light to medium loads under dead, variable or vibratory conditions, in solid or hollow masonry

APPROVALS/LISTINGS

- G.S.A. Spec A-A-55614
- Contact customer service for approvals

CONSIDERATIONS

- Drill recommended hole diameter



ORDER DETAIL

Order Code	Size	HOLE DIAMETER		Head Diameter	Grip Range	2000 P.S.I.			Head Style	Box Qty.	Master Qty.
		Masonry	Wood / Metal			Tension Hollow Wall	Shear Hollow Material	Tension Cement Block			
6460000	9/32" x 1"	1/4"	9/32"	5/8"	3/16-1/2"	130	250	150	TRUSS	100	1200
6660000	9/32" x 1-5/8"	1/4"	9/32"	5/8"	3/8-1 1/8"	130	253	158	TRUSS	100	800
6760000	9/32" x 2-1/8"	1/4"	9/32"	5/8"	7/8-1 5/8"	130	274	154	TRUSS	100	800
6860000	9/32" x 2-5/8"	1/4"	9/32"	5/8"	1 3/8-2 1/8"	130	238	163	TRUSS	100	500
6960000	9/32" x 3-1/8"	1/4"	9/32"	5/8"	1 7/8-2 5/8"	130	228	150	TRUSS	100	500

INSTALLATION

- 1 Drill hole slightly deeper than fastener length.
- 2 Clean hole of debris.
- 3 Tap "Uni-Tap" into place through material to be fastened.

